Dalhousie University, Department of Facilities Management Confined Space Inventory Form

Building: <u>Tupper F200</u>	Room Number: MR	Date: June 19, 2013			
Confined Space No: F200 - SS - 02	Confined Space Class:				
Description of Space: <u>Sewage sump pumps.</u>					
Confined space is located in the mechanical area doors 24 and 25 and can be accessed through either door.					
Construction Material: Concrete with aluminium covers.					
Method of Entry: <u>By ladder.</u>	No. of Access / Egress Points: 1				
Dimensions of Access / Egress Opening:					
Length: 34.0 inches Width: 22.0 inches D	epth: <u>10.0 ft. approx.</u> Diame	er: 00.0 inches			
Type of Work Normally Conducted in Space: Maintenance and repair on pumps.					
Frequency of Work Performance: As required.					
Reference Atmospheric Testing: CO ppm	H ₂ S ppm O ₂	% LEL%			
Other:					

Potential Hazards				
List all hazards near the access / egress opening(s) or in the confined space that must be controlled to ensure employee safety.				
Potential Hazards	Recommended Control Measures			
Oxygen Hazard:				
Electrical Hazards:				
Shock from power cords for pumps	Disconnect and isolate power source. Keep cords out of water.			
Mechanical Hazards:				

Physical Hazards:	
Water in bottom of pit.	
Chemicals Hazards:	
Chemicais Hazarus.	
Diological	
Biological:	
Sewage	
Additional Comments:	

Photographs





Photo Numbers: <u>2013 – 06 – 19 (1414)</u>

<u>2013 – 06 – 19 (1414)</u>

List Emergency Procedures:		
Assessment Conducted By:		
Signature:	_	
Phone number:	-	
Date:		